

RESISTANCE THERMOMETER

Measuring insert: Interchangeable

Type: RT-BC-P

Sheet No.
2-3 V2.1

5452-E010321V3.1




Application:

- For measuring temperatures in the food, Pharmaceutical, cosmetic and chemical/ technical industries

Properties:

- Sensor: Pt100 and Pt1000 in acc. with IEC 60751
- Measuring insert: Interchangeable
- Mechanical and thermal stress in acc. with DIN 43772
- Parts with media contact in EN 1.4404 (AISI 316L)
- Withstands media temperatures of up to max 250°C
- Withstands vibrations
- Quick reaction time
- Degree of protection is determined by the electrical connection; in this case IP65
- After the sensor has been fitted, the plug can be adjusted to point in the desired direction
- Approved by: GOST, TRCU on request.



MECHANICAL SPECIFICATIONS

Protective sheath: -----
EN 1.4404 (AISI 316L) max. 850°C

Immersion Tube Diameter Ø: -----
Ø5 mm / Ø6 mm / Ø8 mm / Ø12 mm
Special

Extension length L2: -----
30 mm
50 mm
Special

Immersion Tube length L1: -----
20 mm
35 mm
50 mm
Special

Process attachment: -----
3/4" APC
1 1/2" DN38, ISO2852
2" DN 51, ISO2852
Special

Surface area of parts with media contact: --
Mechanically polished <0,8 µm
Electro-polished <0,5 µm

ELECTRICAL SPECIFICATIONS

---Cable (pre-mounted in Plug):
SS (Silicone-Silicone) max. 180°C
SBS (Silicone-Inner Braided-Silicone)
TBT (Teflon-Inner Braided-Teflon)
None

---Cable length [m]:

---Sensor element:
1xPt100
2xPt100
1xPt1000 (only cl. B 1/1 and cl. A)
2xPt1000 (only cl. B 1/1 and cl. A)

---Number of conductors:
2-wire (recommended only for Pt1000)
3-wire
4-wire

---Media temperature max:
+180°C
+250°C

---Tolerance in acc. with IEC 60751:
Type A DIN (i.e. ±(0,15+0,002xTactual) °C)
Type B 1/1 DIN (i.e. ±(0,3+0,005xTactual) °C)
Type B 1/3 DIN (i.e. ±(0,1+0,0017xTactual) °C)
Type B 1/6 DIN (i.e. ±(0,05+0,00083xTactual) °C)
Type B 1/10 DIN (i.e. ±(0,03+0,0005xTactual) °C)

Link for further information: [Pt100 Tolerance](#)

RESISTANCE THERMOMETER

Measuring insert: Interchangeable

Type: RT-BC-P

Sheet No.
2-3 V2.1

5452- E010321V3.1



Calibration:

Temperature calibration are used to verify and certify the sensor to have the correct accuracy. We can do either: "In house" or "Accredited" calibration. Accredited is certified by 3.e part. Normally we do a calibration in 3 points.

Enhanced performance services:


Cold applications (below -50°C) will influence the material and the measurement. CRYO treatment is needed to ensure a correct and working sensor down to -196°C.

A sensor will always drift over time, especially when there are high temperature fluctuations.

With "Ageing treatment" we stabilize the sensor to ensure a minimum drift over time. The benefits are long term stability, more correct measurement and easier planning of calibration periods.

Documentation:

Please order the correct documentation when ordering the sensor.



SIGNAL PROCESSING

Enclosure

Marine Box (112x82x42mm) -----

ABS Box (82x80x56mm) -----

NONE -----

Programmable mounted transmitter:

Measuring range min/max: -200/+850°C

Output: 2-wire, 4-20 mA

Min. span: 25°C

Ambient temperaturer min/max: -40/+85°C



[5333A Uninsulated for RTD](#)

[5333D EEX Uninsulated for RTD](#)

[5332A Uninsulated for RTD](#)

[5332D EEX Uninsulated for RTD](#)

[5331A Galvanic Isolated RTD / TC](#)

[5331D EEX Galvanic Isolated RTD / TC](#)

[5335A Hart 5 Protocol Standard](#)

[5335D Hart 5 Protocol CSA, FM, ATEX, IECEx](#)

[5337A Hart 5 & 7 Protocol](#)

[5337D Hart 5 & 7 Protocol CSA, FM, ATEX, IECEx](#)



Transmitter Type:			
4 mA =	C°	20 mA =	C°

Link to further information:

[Transmitter Overview](#)

[Programmable rail mounted transmitter](#)



CALIBRATION

---Calibration:

In house (Span -33°C - +700°C)

Accredited – in laboratory (-196°C - +1200°C)

1.	Point	°C
2.	Point	°C
3.	Point	°C

More point on request

Enhanced performance services

-----Cryo treatment.

For temperature sensor under -50°C

-----Ageing:

For long term stability.
Secure minimum drift of sensor accuracy

-----Documentation

Certificate: 3.1 Material
Certificate of origin
Certificate of conformity
Certificate of GOST

Other on request