RESISTANCE THERMOMETER **Measuring insert: Fixed.**	**Type: RT-RC1-C**	5751-E050624V2.2

Application:

- For measuring temperatures in the food industry and the pharmaceutical, cosmetic and chemical/ technical industries



Properties:

- Sensor: Pt100, 2xPt100, Pt1000 in acc. with IEC 60751
- Measuring insert: Interchangeable
- Mechanical and thermal stress in accordance with DIN 43772
- Process attachment: Flange
- Outer protective sheath and flange: Stainless acid-proof steel
- Stands media temperatures of up to max. 250°C
- Stands ambient temperatures of up to max. 250°C
- Stands vibrations
- Quick reaction time
- IP67

MECHANICAL SPECIFICATIONS

Protective sheath: ----------
EN 1.4404 (AISI 316L), max. 850°C

Immersion tube diameter [mm]: ----------
Ø5
Special

Extension length L2 [mm]: ----------
30
Special

Immersion tube length L1 [mm]: ----------
20 / 35 / 50
Special

Process attachment: ----------
Clamp: 3/4" APC
11/2" DN38, ISO2852
2" DN51, ISO2852
Special

Surface area of parts with media contact: --
Mechanically polished <0,8 µm
Electro-polished <0,5 µm

ELECTRICAL SPECIFICATIONS:

----Sensor type:
1xPt100
2xPt100
1xPt1000

-----Number of conductors:
2-wire
3-wire
4-wire

----Temperature range min/max:
-50/+250°C
Special

---Tolerance in acc. with IEC 60751:
Type A DIN (i.e.±(0,15+0,002xTactual)°C)
Type B 1/1 DIN (i.e.±(0,3+0,005xTactual)°C)
Type B 1/3 DIN(i.e.±(0,1+0,0017xTactual)°C)
Type B 1/6 DIN(i.e.±(0,05+0,00083xTactual)°C)
Type B 1/10 DIN(i.e.±(0,03+0,0005xTactual)°C)

---Cable type:
Cable type SS (Silicone-Silicone) max. 180°C
Cable type SBS (Silicone-Braid-Silicone) max. 180°C
Cable type TBT (Teflon-Braid-Teflon) max. 250°C
Special

---Cable length L3 [mm]
2 / 4 / 6 / 10 m
Special

Link for further information: Pt100 Tolerance

Date:

Part No.:

Kjaerulf Pedersen a/s, Taastrupgaardsvej 8-10, DK-2630 Taastrup, Tel.: +45 39760203, sales@kp-as.com, www.kp-as.com

This is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability.

RESISTANCE THERMOMETER **Measuring insert: Fixed**	**Type: RT-RC1-C**	5751-E050624V2.2

Calibration:
Temperature calibration are used to verify and certify the sensor to have the correct accuracy. We can do either: “In house” or “Accredited” calibration. Accredited is certified by 3.e part. Normally we do a calibration in 3 points.

Enhanced performance services:
Cold applications (below -50°C) will influence the material and the measurement. CRYO treatment is needed to ensure a correct and working sensor down to -196°C.

A sensor will always drift over time, especially when there are high temperature fluctuations.
With “Ageing treatment” we stabilize the sensor to ensure a minimum drift over time. The benefits are long term stability, more correct measurement and easier planning of calibration periods.

Documentation:
Please order the correct documentation when ordering the sensor.



SIGNAL PROCESSING

Enclosure

Marine Box (112x82x42mm) ----------

ABS Box (82x80x56mm) ----------

None ----------

Programmable mounted transmitter:

5333A Uninsulated for RTD
5333D EEX Uninsulated for RTD
5332A Uninsulated for RTD
5332D EEX Uninsulated for RTD
5331A Galvanic Isolated RTD / TC
5331D EEX Galvanic Isolated RTD / TC
5335A Hart 5 Protocol Standard
5335D Hart 5 Protocol CSA, FM, ATEX, IECEx
5337A Hart 5 & 7 Protocol
5337D Hart 5 & 7 Protocol CSA, FM, ATEX, IECEx

Transmitter Type:			
4 mA =	C°	20 mA =	C°

5350A Profibus standard
5350B Profibus ATEX, FM and CSA

Link to further information:

Transmitter Overview

Programmable rail mounted transmitter

CALIBRATION

None ----**Calibration:**
In house (Span -33°C - +700°C)

Accredited – in laboratory (-196°C - +1200°C)

1.	Point	°C
2.	Point	°C
3.	Point	°C

More point on request

Enhanced performance services

---**Cryo treatment.**
For temperature sensor under -50°C

---**Ageing:**
For long term stability.
Secure minimum drift of sensor accuracy

---**Documentation**
Certificate: 3.1 Material
Certificate of origin
Certificate of conformity

Other on request

Save Print Submit

Date:

Part No.:

Kjaerulf Pedersen a/s, Taastrupgaardsvej 8-10, DK-2630 Taastrup, Tel.: +45 39760203, sales@kp-as.com, www.kp-as.com

This is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability.